

## PORTABLE FIRE EXTINGUISHER



### 2.0kg HALOTRON STORED PRESSURE FIRE EXTINGUISHER (SETSCO APPROVED)

#### Specification :

- Capacity : 2 kg
- Extinguishing Medium : Halotron I
- Propellant Type : Argon
- Fire Rating : 5A,34 B
- Class of Fire : A,B
- Discharge Time : 6.1 sec
- Discharge Range : 3 m
- Working Pressure : 6.9 bar
- Working Temperature : -20Deg C to +60 Deg C
- Finishing : RAL 3001
- Hose Length : 440 mm
- Size : Dia. 98 x 455(H) mm
- Gross Weight : 3.76 kg

### 4.0kg HALOTRON STORED PRESSURE FIRE EXTINGUISHER (SETSCO APPROVED)

#### Specification :

- Capacity : 4 kg
- Extinguishing Medium : Halotron I
- Propellant Type : Argon
- Fire Rating : 8A,55 B
- Class of Fire : A,B
- Discharge Time : 9.3 sec
- Discharge Range : 5 m
- Working Pressure : 8.63 bar
- Working Temperature : -20Deg C to +60 Deg C
- Finishing : RAL 3001
- Hose Length : 440 mm
- Size : Dia. 139 x 460(H) mm
- Gross Weight : 6.53 kg

## **6.0kg HALOTRON STORED PRESSURE FIRE EXTINGUISHER (SETSCO APPROVED)**

### **Specification :**

- Capacity : 6 kg
- Extinguishing Medium : Halotron I
- Propellant Type : Argon
- Fire Rating : 13A,70B
- Class of Fire : A,B
- Discharge Time : 11 sec
- Discharge Range : 5 m
- Working Pressure : 8.63 bar
- Working Temperature : -20Deg C to +60 Deg C
- Finishing : RAL 3001
- Hose Length : 440 mm
- Size : Dia. 181 x 505(H) mm
- Gross Weight : 9.74 kg



### **Features :**

- Outdoor UV Resistance Polyester Powder Coated
- Heavy Duty Hose
- Suitable to Use on Live Electrical Equipment
- Effective Suppression of Class A & B Fires
- Use in Clean Environment
- Replacement of Halon 1211

**Standards :** Manufactured in accordance with BS EN 3-7 : 2004 +A1 :2007 & BS EN 3-8 : 2006

**Approvals:** SETSCO ( SG )

**Origin :** Made in Singapore