

ABC DRY POWDER PORTABLE FIRE EXTINGUISHER



| Model | EED-1 | EED-2 | EED-3 | EED-4 | EED-6 | EED-9 | EED-12 | |
|-----------------------------|--|------------------------|----------|----------|----------|----------|----------|--|
| Type | Stored Pressure Type | | | | | | | |
| Extinguishant | Dry Powder | | | | | | | |
| Capacity | 1.0 kg | 2.0 kg | 3.0 kg | 4.0 kg | 6.0 kg | 9.0 kg | 12.0 kg | |
| Propellant | Nitrogen (N ₂) | | | | | | | |
| Valve | Controllable Chrome Plated Brass Valve with Pressure Indicator | | | | | | | |
| Body Diameter | 80 mm | 110 mm | 130.2 mm | 130.2 mm | 158 mm | 178 mm | 188 mm | |
| Overall Height | 326 mm | 373 mm | 425 mm | 515 mm | 525 mm | 585 mm | 702 mm | |
| Approx. Full Weight | 1.9 kg | 3.4 kg | 5.4 kg | 7.2 kg | 9.6 kg | 13.5 kg | 18.0 kg | |
| Working Temp. Range | - 20°C to + 60°C | | | | | | | |
| Working Pressure | 12 Bar @ 27°C | | | | | | | |
| Test Pressure | 25 Bar | | | | | | | |
| Burst Pressure | Exceeds 69 Bar | | | | | | | |
| Approx. Discharge Range | 2 m | 2.5 m | 4 m | 5 m | 5 m | 7 m | 7 m | |
| Approx. Discharge Time | 7 sec | 12 sec | 14 sec | 20 sec | 16 sec | 18 sec | 30 sec | |
| Fire Rating | 5A:34B | 13A:55B | 13A:89B | 21A:113B | 43A:233B | 43A:233B | 43A:233B | |
| Coating (Internal) | Stoving Epoxy Primer | | | | | | | |
| Paint Finishing | RAL 3000 Flame Red Polyester Powder Coating | | | | | | | |
| Mounting | Plastic Vehicle Bracket* | Metal 'L' Wall Bracket | | | | | | |
| Manufactured & Certified to | SS EN3:2012 | | | | | | | |

In accordance to our company's policy of continuous improvement, specifications are subject to change without notice.